

Conventional UT & TOFD Cables



Select from a variety of cable grades to meet your specific application needs

Standard lengths 3' (1 m), 4' (1.2 m), 6' (1.8 m).

All cables are 50 ohms impedance unless otherwise specified

Contact us for special or customized cables, both length and connector type can be customized.

Armored Stainless Steel (SSA)

- All below specified cables can be ordered with
Armored stainless steel
- Interlocking stainless steel jacket provides flexibility,
protection and ruggedness in heavy industrial settings
- Can be ordered in lengths up to 5m.
- Armored cables can be used for high temperature applications.

Standard Cable

- BNC to BNC Cable
- BNC to Microdot® Cable
- BNC to Right-Angle Microdot® Cable
- Small Lemo 00 to BNC Cable
- Small Lemo 00 to Microdot® Cable
- Large Lemo 1 to BNC Cable
- Large Lemo 1 to Microdot® Cable
- Large Lemo 1 to Small Lemo 00 Cable
- Large Lemo 1 to Large Lemo 00 Cable



989/16/2, FIRST FLOOR NEAR GAYATRI ICE INDUSTRIES,
MAKARPURA, VADODARA, GUJARAT - 390010



sales@ucomax.com



www.ucomax.com



+91 63588 33112