


MATERIAL PRIME

Metallurgical Image Analysis Software



Material Prime is a modular quantitative image analysis software Specific to Metal Industries.

INTRODUCTION OF MATERIAL PRIME

MATERIAL PRIME software designed for industrial materials, Scientists, Metallurgists, Laboratory technicians, and R & D engineers who need improved solutions for quality control and product development.

MATERIAL PRIME is computer-aided quantitative analysis results follows strictly ISO & ASTM technical standards.

The software is powerful to handle different image format BMP, TIFF, GIF, JPEG etc. It support many cameras, USB 2.0 & USB 3.0, devices, TWAIN input devices.

This exceptional software produces as much as 80% more picture points in image window than competitive software.

The image processing technique will streamline image capture, measurement and enhancement, while improving the accuracy of your results. Live measurement saves lot of your time



MODULES OF MATERIAL PRIME

Some of the major modules in MATERIAL PRIME are as follows:

CAMERA

One can select different display/capture sizes along with other setting like white balance, brightness, contrast, Hue, Saturation can be changed on live displayed image. Once all setting are done, image can be captured in appropriate folder for appropriate analysis.

CALIBRATION

Calibration should be performed on all the objectives of the microscope, where Digital Camera is installed. Calibration should be performed only when all hardwares are finally fixed. In case of readjustments or replacement of any part, calibration should be done again.

MEASUREMENT

With the Measurement module one can obtain measurement on manually drawn lines on traces, shapes or by outlining an object Which can be accumulated and logged on to the results worksheet from where they can be stored to a file, printed or transferred to spread sheet for further analysis or statistics.

GRAIN SIZE

This module can quickly perform automatic, objective and repeatable grain size analysis to industrial standards to determine ferritic & austenitic grain size in steed, international method ASTM E-112, E-93, E1181 are used.

POROSITY

Pores, due to their contrast with the rest of the image, are relatively easy to detect automatically the module allows a user to recognize and measure the porosity in the material according to ASTM B276 Standard Thresholding readily accomplished using gray scale techniques. The dark phase of porosity is detected in red biplanes.

SEGMENTATION

Segmentation is a method of image partitioning on the intensity / grayscale range of its parts. Since a phase is detected and its area is estimated on the basis of its intensity / grayscale, an option for delineating phases from the histogram is also provided. Multiple phases are identify by colored overlays and can be simultaneously displayed in the same field of view.

DECARBURIZATION

The module is used to determine the depth of Decarburization form the changes in structural quality In partial decarburization is where the carbon content is reduced but there is on total Decarburization is measured in work piece to the limit of the limit of the ferritin layer with almost total carbon removal if compliance ASTM E-1077-91 Standard CAMERA GRAIN SIZE CALIBRATION POROSITY MEASUREMENT SEGMENTATION DECARBURIZATION

SG IRON

SG Cast Iron or Nodules are also called DUCTILE IRON or SPHEROIDAL GRAPHITE IRON. Nodules Cast Iron are produce from graphite during Solidification. Ductile Iron Analysis module provides a chance to analyze an image on the basis of ASTM A-247-67, ISO-945-1.

GRAY IRON


Grey Iron or grey Cast Iron is a type of Cast iron that has a graphitic micro structure. Grey iron analysis module provides a chance to analyze an image on the basis of ASTM A-247-67, ISO 945-1

CARBIDE

Iron carbide or Cementite is an intermetallic component of iron and Carbon. While iron Carbide as present in most steels and Cast Iron, it is produced as raw material in the iron carbide process, which belongs to the family of alternative iron making technology.


CAMERA

One can select different display/capture sizes along with other setting like white balance, brightness, contrast, Hue, Saturation can be changed on live displayed image. Once all setting are done, image can be captured in appropriate folder for appropriate analysis.




CALIBRATION

Calibration should be performed on all the objectives of the microscope, where Digital Camera is installed. Calibration should be performed only when all hardwares are finally fixed. In case of readjustments or replacement of any part, calibration should be done again.



MEASUREMENT


With the Measurement module one can obtain measurement on manually drawn lines on traces, shapes or by outlining an object which cannot be accumulated and logged on to the results worksheet from where they can be stored to a file, printed or transferred to spread sheet for further analysis or statistics.



GRAIN SIZE

This module can quickly perform automatic, objective and repeatable grain size analysis to industrial standards to determine ferritic & austenitic grain size in steed, international method ASTM E-112, E-93, E1181 are used. Comprehensive selection of analysis technique are:

- Lineal intercept method
- Abrams three circle method.
- Snyder & graft method.
- Comparison method
- Random intercept method
- Manual grain size. This wizard measures the Grain number, the mean area, mean intercept length, at high speed according to selected method.



SEGMENTATION

Segmentation is a method of image partitioning on the intensity / grayscale range of its parts. Since a phase is detected and its area is estimated on the basis of its intensity / grayscale, an option for delineating phases from the histogram is also provided. Multiple phases are identified by colored overlays and can be simultaneously displayed in the same field of view. The results and images displayed get stored in to distinguish the phases prominently. Various filters like Despeckle, Smoothing etc can be used before doing the phase.

A histogram for gray scale images is created once you open the Segmentation Module. The X-axis represents intensity scale between 0-255. The Y-axis represents number of pixels in the image. analysis. the industrial standard automatically.

HISTOGRAM:


Phase allows the user to designate up to ten different threshold settings to identify material phases and name each of these phases. The color between two lines signifies a particular phase.

INTENSITY:

The Gray Intensity range of the current phase gets display continuously in the dialogue box.


SELECTED PHASE:

This property enable the user to know the percentage area of a specific range of intensity just by clicking the mouse. All previous operations have to be deleted and Preview should be on None.



POROSITY

Pores, due to their contrast with the rest of the image, are relatively easy to detect automatically the module allows a user to recognize and measure the porosity in the material according to ASTM B276 Standard Thresholding readily accomplished using gray scale techniques. The dark phase of porosity is detected in red bitplanes. The total number of pores are counted along with their percentage of minimum & maximum size are also identified and reported. The whole process is fully automatic.




DUCTILE IRON/NODULARITY

Ductile Iron, also known as ductile cast Iron, Nodular Cast Iron, Spheroidal Graphite Iron & SG Iron is a type of Graphite rich cast Iron. We use image processing algorithms like segmentation using Global thresholding, Boundary detection and Artificial Neural Network. Nodules touching boundaries are excluded in analysis. Artifacts less than 10 microns are excluded. Non-nodules are separated from Non-nodules on predefined spherodicity. For analysis of SG Iron, we compute quality parameters such as Nodules counts, Nodule Size (designated by Arabic no. 1 to 8), Nodule form (designated by roman number I to VI). All analysis are done with single button push.

In the second step, etched samples are analysed. The software automatically calculates the percentage Graphite, Pearlite once the analysis completed. All data of Non-etched and etched sample is appended into a results spreadsheet directly with in the image analysis software.

Reports containing relevant analysis data and associated images are generated with one button push.




SG Iron



Process Etched Sample

Back



Next




Non-Etched Image



Etched Image





Graphite, Pearlite, Ferrite %



Final Report



GRAY IRON/GRAFITE FLAKES

Gray Iron or Gray Cast Iron is the graphite flakes structure that is created during the cooling process. It is named after the gray color of the fracture its forms, which is due to the presence of graphite. The application measures graphite length in gray iron. The shorter the A type graphite flakes, the highest the strength and better the ductility. The automatic, one button computer program quantitatively analyses the graphite length in Metallography. The graphite sizes are reported in 1-8 classes of size according to ASTM 247-67 or ISO 945 -1 standards. It categorizes graphite flakes from namely type A,B,C,D & E in microstructure sample on the basis of orientation. The percentage of pearlite is calculated by excluding the graphite area. The matrix of pearlite , Ferrite , graphite are reported in etched sample . Report is generated with specific international standards chosen by the user.





DECARBURIZATION

The module is used to determine the depth of Decarburisation form the changes in structural quality In partial decarburisation is where the carbon content is reduced but there is on total Decarburisation is measured in work piece to the limit of the limit of the ferritin layer with almost total carbon removal if compliance ASTM E-1077-91 Standard





COATING THICKNESS

Plating or coating thickness is determined by cross-sectional microscopy method. The specimen is cross-sectioned, mounted, polished and microscopically evaluated for measuring the plating or coating thickness, sometimes, etching of the core base metal may be necessary to accurately measure the coating or plating thickness. The test method covers measurements of the local thickness of metal and oxide coatings by the microscopical examination of cross sections using an optical microscope. Under good condition, when using an optical microscope, the method is capable of giving an absolute measuring accuracy of 0.8 mm. this with determine the suitability of the method for measuring the thickness of thin coating.







SPHERODIZATION

This module is designed to analyze spheroidal graphite (nodules). The nodules are separated from non-nodules on predefined spheroidicity. Nodules acquire blue color and non-nodule get red color. Nodules from (designated by Roman numbers from I to VI) and size (designated by Arabic numbers 1 to 8) are reported along with the calculated nodules/sq mm.



CARBIDE BANDING

Iron carbide or Cementite is an intermetallic component of iron and Carbon. While iron Carbide as present in most steels and Cast Iron, it is produced as raw material in the iron carbide process, which belongs to the family of alternative iron making technology.



NON METALLIC INCLUSION

- Using Material Prime software a user can identify four types of inclusion..
- SULFIDE TYPE (A TYPE), ALUMINA TYPE (B TYPE)
- SILICATE TYPE (C TYPE), GLOBULAR TYPE (D TYPE)
- Each type is further divided into Thin and Heavy, based on the width parameters.

Spherodization

Step 1
Select Direction
• Horizontal • Vertical

Step 2 / Step 4
Type A (Sulfide) Separation

Step 3 / Step 5
Compute

Others:
Sulphides:

Back Report Help



SETTINGS

The Module SETTING is designed to set various parameters for first time when software is installed. The setting options are available to choose ISO/ASTM standard calibration, setting in report format, setting of various parameter on printed image in report. Once all settings are done, you need one button click for all Analysis. All settings are stored till you change them in future. Do not change them in routine, it is not necessary.



If click on settings icon, new UI will open. The platform help you to decide the shortcuts of your working. If you choose any of radio button correctly, your working will have no scope for mistake and software will be one button working


1. Report Type Options are available to get report either in ASTM or ISO formats. Choose any of them, this will be automatically be in default setting till you modify in future.
2. Set Default Use Our software give a choice to work either on live display images or you can capture first all images and work on them later.
 - It means you want to work on live images.
 - This is for working on stored / captured images.
3. Select Calibration Choose calibration which are available in stored data. Usually we do all work on 100X objective in Cast Iron.
4. Set 100 Micron Line If you need Scale bar on image choose the fourth options available:
 - To Show boundary click it if you want to see contour around the graphite.
 - Click on Show Number if you want to display counting on graphites.
5. Set Gallery Path Gallery path is set by default. But if you need to change this path, you can do necessary changes.
6. SG Iron Various options are available to show different parameters on Nodules. Choose it if you require otherwise contour is created by default.
7. Aspect Ratio This is usually fixed. But change only if required. 8.1 Two templates are available
 - Report with chemical composition and physical analysis properties composition.
 - Report without chemical & physical properties

GALLERY

Four Folders are available to view any Captured images.


The folders are:

1. Measurement
2. Segmentation
3. Grain Size
4. Porosity
5. Decarburization
6. SG Iron
7. Gray Iron



SAVE REPORT

All reports are saved in the folder and can be retrieve anytime in future.



989/16/2, FIRST FLOOR NEAR GAYATRI ICE INDUSTRIES,
MAKARPURA, VADODARA, GUJARAT - 390010



sales@ucomax.com



www.ucomax.com



+91 63588 33112